

Electrical Metallic Tubing (EMT)

Electrical Metallic Tubing (EMT) provides the best protection for wire and cable in all kinds of installations and applications.

Because of the lightweight material, BlueSteel Rapid-Pull EMT conduit allows for easy on-site installation and bending, saving money on labor costs.

BlueSteel Rapid-Pull EMT products go through QA/QC procedures to ensure the highest quality and hassle-free wire pulling.



**Smooth, low-friction
 epoxy coating inside**

Easy to bend

Tested to meet UL 797 standards for:

- Bending characteristics
- Corrosion resistance
- Cold bending

UL/cUL listed in accordance to UL797 & ANSI C80.3 Standards • UL File Number E497191

Cat.No.	Trade Size		Nominal Outside		Nominal Wall Thickness		Approx. Wt. Per 100 Ft. (30.5M)		Qty. In Master Bundle	
	US	Metric	in.	mm	in.	mm	lb.	kg	ft.	pcs
EMT15U	1/2	16	0.706	17.93	0.042	1.07	30	13.6	7000	700
EMT20U	3/4	21	0.922	23.42	0.049	1.25	46	20.9	5000	500
EMT32U	1	27	1.163	29.54	0.057	1.45	67	30.4	3000	300
EMT40U	1-1/4	35	1.51	38.35	0.065	1.65	101	45.8	2000	200
EMT50U	1-1/2	41	1.74	44.20	0.065	1.65	116	52.6	1500	150
EMT60U	2	53	2.197	55.80	0.065	1.65	148	67.1	1200	120
EMT75U	2-1/2	63	2.875	73.03	0.072	1.83	216	98	610	61
EMT80U	3	78	3.5	88.90	0.072	1.83	263	119.3	510	51
EMT90U	3-1/2	91	4	101.60	0.083	2.11	249	158.3	370	37
EMT100U	4	103	4.5	114.30	0.083	2.11	393	178.2	300	30

Outside Diameter Tolerances

+/- .005 in. (.13mm) for trade sizes 1/2" (16mm) through 2" (53mm), +/- .010 in. (.25mm) for trade sizes 2 1/2" (63mm)
 +/- .015 in. (.38mm) for trade sizes 3" (78mm), +/- .020 in. (.51mm) for trade sizes 3 1/2" (91mm) and 4" (103mm)

NOTE: Length = 10 ft. (3.05m) with a tolerance of +/- .25" (6.35mm)