

# PVC Coated Rigid Conduit



- Hot-dip galvanized steel or aluminum conduit
- 40 mil PVC coating on exterior
- 2 mil grey urethane coating on interior and threads
- Color-coded thread protectors
- Couplings shipped with conduit are packaged separately
- UL File Number E497191

## ELECTRICAL RIGID METAL CONDUIT WITH POLYVINYL CHLORIDE (PVC) COATING VERIFIED FOR PVC ADHESION PERFORMANCE VERIFIED BY UL DYJC

Cat. No .		Trade Size	Metric Size	Wall Thickness With PVC(in)	OD With PVC(in)	ID (in)	LENGTH Without Coupling
Steel	Alum.						
RSC15P	RAC15P	1/2"	16	0.14	0.92	0.63	9' 11 1/4"
RSC20P	RAC20P	3/4"	21	0.15	1.13	0.84	9' 11 1/4"
RSC25P	RAC25P	1"	27	0.17	1.40	1.06	9' 11"
RSC32P	RAC32P	1-1/4"	35	0.17	1.74	1.39	9' 11"
RSC40P	RAC40P	1-1/2"	41	0.18	1.98	1.62	9' 11"
RSC50P	RAC50P	2"	53	0.19	2.46	2.08	9' 11"
RSC65P	RAC65P	2-1/2"	63	0.23	2.96	2.49	9' 10 1/2"
RSC80P	RAC80P	3"	78	0.25	3.58	3.09	9' 10 1/2"
RSC90P	RAC90P	3-1/2"	91	0.26	4.08	3.57	9' 10 1/4"
RSC100P	RAC100P	4"	103	0.27	4.58	4.05	9' 10 1/4"
RSC125P	RAC125P	5"	129	0.29	5.64	5.07	9' 10"
RSC150P	RAC150P	6"	155	0.31	6.71	6.09	9' 10"